

STANDARD SPECIFICATION:

(Custom Modular Home)

EXTERNAL:

- Engineered design
- C2 cyclone rating as standard
- 2600 high walls (2550 ceiling height)
- 700mm nominal FFL
- Insulated walls and under roof
- HDG steel stumps
- Glass and aluminium windows/doors with fly screens
- James Hardies Primeline Chamfer cladding
- Colourbond fascia, gutters and roofing
- Modwood composite decking
- Hardwood step treads oiled
- Dulux weather shield or equiv. external paint
- AC external unit and HWS on welded chassis brackets
- 125L storage HWS

* Please note at contract stage a detailed item and colour selections booklet will be completed which goes through fixtures and finishes in more detail.

INTERNAL:

- Flush set gyprock ceilings
- VJ paneling to all walls except wet areas
- 6mm vilaboard flush set to wet area walls
- Bathroom tiled floor with 100mm skirting tiles, shower walls tiled to 2000 and 300mm splash to vanity/ldy. 600 Splash to kitchen
- Built in robe to bedroom with 1 x mirror and vinyl sliding doors OR bench seat with high shelf over
- Wall hung vanity basin (builders range)
- Mirror shaving cabinet to match vanity width
- Quality fixtures including all mixer taps and back to wall toilet suite (builders range from Reece)
- 1200h nib wall to shower with 10mm fixed glass over, 1200h shelf wall to rear of shower
- Split system air conditioning to living area
- White DC ceiling fan, white LED downlights, exhaust fan in bathroom, GPO's throughout, internal sub board
- Vinyl planking to main area
- Interior walls/skirting in Dulux Wash & Wear premium paint or equiv.
- Interior doors & frames in Aquanamel gloss of wall colour